



# Samples Specifications

Model No     EA-01L4F05


## Power LED –Green

| Client Signature |            |       | Company Signature |          |          |
|------------------|------------|-------|-------------------|----------|----------|
| Approved         | Acceptance | Stamp | sales             | Approved | Creation |
|                  |            |       |                   |          |          |



***E+A LED's***

## ■ Dimension Drawing



Note.:

1. All dimensions are in millimeters.
2. All dimensions without tolerances are for reference only
3. The package material of the body is heat-resistance polymer, and the plating material of the lead frame is Ag.

# Photometric Luminous Flux Bin Structure

## Characteristics for P001L4 1W series

### 1. Typical Electrical & Optical Characteristics at $I_F=350\text{mA}$ , $T_A = 25^\circ\text{C}$

| Parameter          | Symbol        | Value      |      |                    | Unit |
|--------------------|---------------|------------|------|--------------------|------|
|                    |               | Min.       | Typ. | Max.               |      |
| Luminous Flux      | $\Phi_V$      | 60         | 66   | 70                 | lm   |
| Wavelength         | CCT           | 520        |      | 530                | K    |
| Forward Voltage    | $V_F$         |            | 3.2  |                    | V    |
| View Angle         | $2\Theta$ 1/2 | Lambertian | 140  | deg.               |      |
| Thermal resistance | $R_{J-B}$     | 12         |      | $^\circ\text{C/W}$ |      |
|                    |               |            |      |                    |      |

### 2. Absolute Maximum Ratings

| Parameter             | Symbol    | Value   | Unit             |
|-----------------------|-----------|---------|------------------|
| Forward Current       | $I_F$     | 350     | mA               |
| Power Dissipation     | $P_D$     | 1.6     | W                |
| Junction Temperature  | $T_J$     | 125     | $^\circ\text{C}$ |
| Operating Temperature | $T_{opr}$ | -30~80  | $^\circ\text{C}$ |
| Storage Temperature   | $T_{stg}$ | -30~120 | $^\circ\text{C}$ |
| ESD Sensitivity       | -         | 1000    | V HBM            |

#### Notes:

- The measured value is tested by an integrator system.
- Tolerance of measurement of luminous flux  $\pm 10\%$
- Tolerance of measurement of CCT  $\pm 5\%$
- Tolerance of measurement of forward voltage  $\pm 0.05\text{V}$
- R is measured with an Xpower Star PCB.
- Do not drive at rated current more than 5 sec. without heatsink for Xpower emitter series.

## Wavelength Characteristics, $T_A=25^\circ\text{C}$

Fig.1 RELATIVE INTENSITY VS. WAVELENGTH




Fig.2 FORWARD CURRENT DERATING CURVE




Fig.3 FORWARD CURRENT VS. FORWARD VOLTAGE




Fig.4 RELATIVE LUMINOUS INTENSITY VS. AMBIENT TEMPERATURE




Fig.5 RELATIVE LUMINOUS INTENSITY VS. FORWARD CURRENT (at  $T_j=25^{\circ}\text{C}$ )




Fig.6 RADIATION DIAGRAM

